

METHOD AND APPARATUS FOR COPY PROTECTING VIDEO CONTENT AND PRODUCING A REDUCED QUALITY REPRODUCTION OF VIDEO CONTENT FOR PERSONAL USE

By Inventor:

Robert Allan Unger

TECHNICAL FIELD

[0001] The invention described herein relates to methods and apparatus for achieving copy protection in video systems. In particular, the invention relates to methods and apparatus for displaying high quality video content but making available for reproduction only a lower quality version of the content.

BACKGROUND

[0002] Conventional implementations of copy protection schemes generally work as follows. An encoded video signal is decoded to provide a "clean signal" which is then modified. By modifying certain characteristics of the clean video signal, a specific type of altered video signal is created. When the altered signal is displayed by a display device, it provides high quality video images. However, distortion is also introduced into the altered signal which does not affect its characteristics when displayed over a display device, such as a television set. However, when the same signal is output into another output device, such as a recording device (e.g., a VCR), the modifications made to the signal are sufficient to seriously degrade the output signal to the point where it is unusable, thereby preventing copying of the original video content.

[0003] Signals can be rendered unusable by a wide variety of approaches. Some common examples include, but are not limited to, blanking a display screen, introducing so much noise into the signal that it cannot be viewed, introducing flashes of light into the displayed images, reducing the picture resolution to a point where it is unviewable, skewing the color balance to an unwatchable level, introducing picture flaws which are irritating to watch thereby making them unviewable. These techniques, as well as many others known in the art, are used to render the signal completely unusable for viewing or reproduction.

[0004] Although the foregoing implementations have the advantage of preventing unauthorized copying of video content, they also have the disadvantage of completely preventing a user from producing personal use copies of his own content. One of the goals of the present invention is to maintain copy protection on existing video content while permitting the creation of "personal use" copies of the same content.

[0005] The present invention relates to improvements in digital content copy protection technology. One particular application of this technology is copy protection for digital video content. There exists a need for a method and system for modifying a video signal such that the signal produces a normal, full quality picture on a display device, but also prevents or inhibits the making of high quality reproductions of the original video signal. Secondly, there is a desire by consumers to make personal use copies of the original video signal, even at reduced quality levels. Therefore, there is a need for producing a modified video signal that enables lower quality reproductions of the original video signal to be made. The purpose of these low quality reproductions is to provide a user of video content with the ability to make a personal use copy of the video content. It should be a feature of the personal use copy that, although it is reasonably acceptable for personal viewing, the quality of the copy is such that there is a noticeable decline in signal quality. In particular, the personal use reproduction should be of low enough quality such that it is not salable to the public. Such a method and apparatus will provide the user with the ability to make personal use copies of video content but discourage copying of video content with the intent of committing wholesale piracy of the content.

[0006] Fig. 1 graphically depicts a "Horizontal Pixel Resolution Spectrum" which figuratively describes a quality spectrum for video content. As discussed herein, signal quality is synonymous with resolution. Pixel resolution refers to x and y (horizontal and vertical) coordinates with a z coordinate representing the number of bits per pixel (thereby defining color and brightness resolution). As is known in the art, different content formats and video signals can be used to provide different levels of signal resolution and quality. For example, digital television using newer HDTV formats can maintain a typical pixel resolution of 1920 pixels per line. Lower resolution digital television formats can maintain pixel resolutions of 1280 per line or 1440 per line. Typical analog television signals provide a somewhat lower picture quality. For example, resolutions on the order of 720 pixels per line are common. Lower resolutions of 350 to 480 pixels per line are

also common. Typical broadcast quality video signal ranges from 400-500 pixels per line and VCR quality signal ranges from 200-400 pixels per line. This spectrum of resolution quality continues to decline until it reaches a level which is essentially worthless and contains no discernible video signal at all.

[0007] Moreover, parameters other than pixels per line can be used to define picture quality. Other parameters like sharpness, contrast, brightness, tint, motion continuity, as well as other related parameters, are important to picture quality. Also, content quality is dependent on audio quality. Therefore, a multitude of parameters affect the content quality.

SUMMARY OF THE INVENTION

[0008] Accordingly, an embodiment of the present invention includes an apparatus for processing a video signal to produce normal quality video for display on a display device and which also inhibits the making of high quality reproductions therefrom while allowing lower quality reproductions to be made. The apparatus includes a first signal modification element that alters the video signal to produce a first modified video signal that is viewable as normal quality video on the display device. Whereas the first modified video signal, produces video copies of an unusable quality. The apparatus further includes a second signal modification element which alters the video signal to produce a degraded second video signal of reduced quality that can be reproduced using a reproduction device.

[0009] In another embodiment the apparatus includes a video decoder for decoding a video signal to provide a clean video signal. The clean video signal is supplied to a first signal modification element which alters the clean video signal to produce a first modified video signal which is of unusable quality when output. Also, the first modified video signal is viewable as high quality video when displayed on a display device. The clean video signal is also supplied to a second signal modification element which alters the clean video signal such that a reduced quality degraded version of the content is produced. This reduced quality degraded version of the content can be output for reproduction. A related embodiment uses a second signal modification element that includes a signal quality reducing means for altering the clean video signal to produce a signal having reduced signal quality.

[0010] Another embodiment includes a method for processing a video signal so that it produces a normal quality picture on a display device but produces a reduced quality copy when reproduced using a reproduction device. The method includes providing a clean video signal, first modifying the clean video signal to produce a first modified signal that is of unusable quality when output for reproduction and is viewable as high quality video when output to a display device, and second modifying the clean video signal to produce a degraded second modified signal having reduced signal quality when output for reproduction.

[0011] Other features of the present invention are set forth in the section entitled: "DETAILED DESCRIPTION OF THE DRAWINGS".

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] For a fuller understanding of the present invention, reference is made to the accompanying drawings in the following Detailed Description. In the drawings:

[0013] Fig. 1 is a diagram showing a horizontal pixel resolution spectrum which presents a spectrum of picture resolution of various display formats.

[0014] Fig. 2 is a block diagram of a conventional copy protection scheme

[0015] Fig. 3A is a block diagram of a copy protection embodiment constructed in accordance with the principles of the present invention.

[0016] Fig. 3B is a block diagram of a switchable copy protection embodiment constructed in accordance with the principles of the present invention.

[0017] Fig. 4 is a block diagram of another copy protection embodiment in accordance with the principles of the present invention .

[0018] Fig. 5 is a flow diagram illustrating a method embodiment in accordance with the principles of the present invention.

[0019] Reference numbers refer to the same or equivalent structural elements throughout the several figures of the drawings.

DETAILED DESCRIPTION OF THE DRAWINGS

[0020] Fig. 2 describes a simplified version of a conventional implementation of an apparatus for processing video signals to inhibit the making of videotape recordings of acceptable, salable quality. An encoded video signal is provided by any of a number of sources. Examples of typical content delivery sources include, but are not limited to, DVD players, VCR devices, set-top boxes, as well as other devices which can receive video signal delivered over the airwaves, through broadband cable, or via satellite. Other content delivery sources of particular interest include internet provided content or content stored on the hard drive of a computer system. Other sources of content can include audio sources, such as radio stations or cable audio broadcasts. In the depicted embodiment, video signals are provided to the apparatus 100. These signals can be provided by an external source (e.g., the internet or other content delivery source) or generated by the device itself (e.g., the device 100 is a DVD player, VCR, set-top box, or other such device). Typically, the content is provided in an encoded form. The encoded signal is then decoded into signals which can be displayed by display devices. In one typical example, a video signal can be encoded using an MPEG encoding and decoding scheme. In such schemes, image data is provided by an image input device, then compressed, and encoded by, for example, a video encoder. Quantization processes and DCT (discrete cosine transform) are usually involved in encoding. Encoded data can be written into a record medium. Typical record medium include, but are not limited to, VCR tape or DVD.

[0021] Decoding follows a reverse process: data is read from the record medium and decoded by, for example, a video decoder. Decoding is preceded by a reverse quantization process and reverse DCT. Image data decoded by the video decoder is output in a displayable format at displayable timing and reproduced and displayed by a display device.

[0022] Fig. 2 is a block diagram of a conventional system 100. An encoded image source 2 provides an encoded image signal 3 which is received by a decoder 4. The decoder 4 decodes the signal and converts it into a usable format referred to herein as a clean signal 5. In a conventional copy protected device, this clean signal 5 is then modified by a signal modification element 7, which changes the signal in a manner which

allows a display device 10 to produce a normal picture, but the modifications also change the signal in a way which causes a reproduction device 11 to produce copies of the video content which are of unacceptable quality. This modified video signal can then output to output devices 10, 11. Output devices include, but are not limited to, display devices such as televisions, digital televisions, high definition televisions (HDTV), computer displays or other display devices 10. Moreover, output devices can include reproduction devices such as VCR's 11 or other content reproduction devices (e.g., writeable CD devices, writeable DVD devices, etc.).

[0023] These basic concepts have been incorporated into numerous methods and apparatus for preventing the copying of video programs. Typical examples are illustrated in U.S. Patent No.'s 4,577,216, 4,907,093, 5,315,448, 5,130,810, as well as others. One common copy protection approach is illustrated in U.S. Patent No. 5,130,810. Such inventions typically modify a video signal by altering aspects of a normal "sync pulse" in a way so that a display device (including, but not limited to a television) produces a normal picture when displayed. However, the modified "synch pulse" wreaks havoc on the picture quality of a recording when a videotape recording of the same modified video signal is made. Such recordings are altered to the extent that they are largely unviewable. Such is the state of ordinary copy protection.

[0024] An embodiment 101 of the present invention is depicted in Fig. 3A. The device depicted in Fig. 3A can include a content source 2, which provides encoded content to a decoder 4, which outputs a clean (decoded) signal 6. This clean signal is a high or normal quality video signal reproduced with all the resolution and fidelity of the original. Although the original encoded signal is depicted here as originating from within the embodiment 101, the encoded signal can be supplied by other sources (e.g., the internet, satellite, cable, radio, other devices or storage locations, etc.). The clean signal can be stored in a buffer or immediately forwarded for display or recording. The depicted embodiment shows the signal being forwarded to a first signal modification element 7, which modifies the signal to create a first modified signal. In the case of video content, the first modified signal is modified such that it can be viewed by a display device 10, but produces an unusable copy when recorded by a reproduction device 11. The inventors contemplate such a copy protection scheme can be applied to audio content as well. The

first modified signal is output through a display output port 8, where it is input into a display device 10 for viewing (or in the case of audio content listening).

[0025] Additionally, and advantageously, the clean signal 6 is also forwarded to a second signal modification element 15, where it is subjected to a second type of signal modification to produce a degraded second modified signal, examples of which will be explained hereinbelow. The second signal modification element can include a signal quality reduction means for producing a lower quality video signal.

[0026] The second signal modification element 15 modifies the clean signal 6 to create a diminished quality second video signal which can be output to a reproduction device 11 (shown here being output to a reproduction output port 16, and connected to the reproduction device 11). For example, the original high quality signal can be resampled to produce video quality on par with that obtained by recording a standard VHS tape (e.g., a two-hour tape) in six-hour mode. The actual quality of the copy will be set by the device manufacturer. The diminished quality signal output to the display device can be achieved using a number of methods. One example means for reducing signal quality is described as follows. If the original clean signal 6 was encoded to display images at a resolution of 1920 pixels per line, the original signal 6 could be resampled to produce a second modified signal 15a having a maximum resolution of, for example, 250 pixels per line. Contemplated embodiments also include second modified signals 15a which have been resampled to resolutions of about 400 or 500 pixels per line. It is to be understood that the pixels per line resolution can be really adjusted to any level with the foregoing specific numbers merely being preferred embodiments. The idea being that the signal quality of the degraded second modified signal 15a is of reduced quality with respect to the original (high or normal quality) signal 6. The degraded second modified signal can be reduced in quality to a level equivalent to broadcast quality signal or VCR recorded quality signal. The preferred embodiment reduces the quality of the original signal to a quality roughly equivalent to that of a standard VHS tape recorded in six-hour mode.

[0027] Additionally, other ways of altering the original video signal 6 to provide the second modified signal may be used. Where an encoded image is encoded using an MPEG format, macroblocks are used as an encoding component of image frames. Each macroblock comprising a 16 x 16 pixel segment within the image. Each pixel has a

luminance component Y and two chrominance components Cr, Cb. Each pixel has a unique luminance value. Whereas, each group of four pixels has a chrominance value for red and also a chrominance value for blue. Thus, a 16 x 16 pixel macro block includes 256 values for luminance and only 64 values for red chrominance and 64 values for blue chrominance. These values for luminance and chrominance are digitally encoded at some resolution (for example, 32-bit resolution). The second signal modification element 15 can be used to reduce the picture quality of the second modified signal 7a output to a reproduction device 11. In one implementation, the pixel resolution can be reduced. For example, using one luminance value for every four pixels instead of for each pixel. The chrominance resolution can also be reduced. For example, using one chrominance value can be used for each 16 pixels rather than one value for each four pixels. These reductions in luminance and chrominance can be further reduced to levels where each macroblock only has four luminance values and only one chrominance value for each, red and blue. Still further reductions in luminance and chrominance resolution can be implemented.

[0028] Another method of producing a second modified signal having lowered picture quality is to encode each of the values, luminance Y, chrominance red Cr, and chrominance blue Cb, having a lower bit resolution. For example, instead of using 32-bit color, 16-bit values can be used. Alternatively, still lower resolution can be used. The same lowering of bit values or brightness resolution can be applied to luminance Y. Additionally, the color values themselves can be altered to non-true values. Slight alterations of this sort will allow the viewer to reproduce reasonable representation of the original, but not to produce a salable quality copy of the original.

[0029] Additionally, where the content includes sound, the sound quality can be reduced in the second modified signal 7a. For example, instead of a 20-bit resolution on the sound track, a 12-bit resolution could be used. Also, sound can be compressed at the high and low ends, introducing a certain amount of distortion, which will allow the user to understand the content but only produce lower quality copies. Also, a certain amount of noise or hiss can be introduced into the audio signal. Additionally, an original sound track in quadraphonic or stereo mode could be reduced to mono.

[0030] Also, the quality of the second modified signal 7a could be reduced by adding white noise to the sound track or to the video signal. Such noise could reduce the

video quality to that of a broadcast signal having a certain amount of “snow” and the audio signal to some slightly distorted level.

[0031] An embodiment 101A of the present invention is depicted in Fig. 3B. The device depicted in Fig. 3B includes a clean (decoded) signal 6. As with the embodiment of Fig. 3A, the clean signal is a high or normal quality video signal reproduced with all the resolution and fidelity of the original. The depicted embodiment shows the signal being forwarded to a first signal modification element 7, which modifies the signal to create a first modified signal. As with the previously discussed embodiment, the first modified signal is viewable on a display device, but produces an unusable copy when recorded by a reproduction device. As with the prior depicted embodiments, the clean signal 6 is also forwarded to a second signal modification element 15, where it is subjected to a second type of signal modification to produce a degraded second modified signal.

[0032] Both the first modified signal and the second modified signal are output into a switch element S that can be used to select which signal is output to an output port O. The signal is then output to an output device D. As disclosed previously, such output devices D can include display devices and/or reproduction devices. Thus, either output (the first modified signal or the second modified signal) can be switchably engaged for output to an output device D.

[0033] Such systems can be incorporated with a wide range of video content sources. Fig. 4 illustrates an embodiment that includes, without limitation, a number of implementations on a single machine 102. For example, a television broadcast signal can be received by an antenna 31, which feeds a signal into a tuner element 41. This signal is then decoded 51 to produce a clean signal 6. Likewise, cable programming 32 can be received and fed into a tuner 42, which selects the appropriate programming, at which point the signal is decoded 52 and a clean signal 6 is produced. Analogously, a satellite signal can be received 33, tuned 43, decoded 53, and used to produce a clean signal 6. Also, content can be directed from the internet 34 into a decoder 54 to produce a clean signal 6. Also, the device 102 can incorporate playback devices 35, such as DVD players, VCR's, and the like. The device 102 can also be interconnected to a network of devices via a connector, such as a standard connector or a 1394 line. A signal can be retrieved from networked devices 35 and decoded 55 (if necessary) to produce a clean signal 6.

Another content source is simply a broadcast radio signal received by an antenna 36, which is passed through a tuner 46, decoded 56, to produce a clean signal 6. Alternatively, content can be taken off of a disk drive 37, either in decoded format or encoded format, which is then processed to produce a clean signal 6. As with the embodiment shown in Fig. 3A, the clean signal is passed through a first signal modification device 7, which provides a first modified signal. As explained with respect to Fig. 2, the first modified signal can be displayed by a display device 10 without distortion. As also explained with respect to Fig. 2, the first modified signal has a distortion introduced which prevents its use by output devices designed to produce copies of the signal. The clean signal 6 is also introduced into a second signal modification element 15, which introduces a measured degradation of the signal allowing reproductions of the content to be produced. The general idea being that the reproductions will be of a watchable but unsalable quality.

[0034] Fig. 5 depicts a flow diagram illustrating aspects of a method embodiment of the present invention. A "clean" signal is provided 61. This means a normal (high) quality signal without any copy protection. Typically, this clean signal is provided by decoding an encoded video signal as described hereinabove. The clean signal is subjected to a first signal modification 63 which alters the clean signal. It can be displayed as a high quality video signal on a display device, but the first signal modification is such that the resulting signal is unsuitable for copying using a reproduction device. This first modified signal can be output to a first output. Also, the clean signal is subjected to a second modification 65 which alters the clean signal to produce a degraded second modified signal having reduced quality relative to the clean signal. This second modified signal can be output to a second output. The second output can be output to a reproduction device for the making of personal use copies. Alternatively, the first and second modified signals can be switchably engaged and output to a selected output device.

[0035] The present invention has been particularly shown and described with respect to certain preferred embodiments and specific features thereof. However, it should be readily apparent to those of ordinary skill in the art that various changes and modifications in form and detail may be made without departing from the spirit and scope of the invention as set forth in the appended claims. In particular, it should be noted that the inventors contemplate that many forms of quality reduction (other than those

specifically mentioned) can be performed by the second modification of the clean signal to achieve a degraded second modified signal in accordance with the principles of the present invention. Further, reference in the claims to an element in the singular is not intended to mean “one and only one” unless explicitly stated, but rather, “one or more”. The examples provided herein are intended to be illustrative rather than limiting. The inventions illustratively disclosed herein may be practiced without any element which is not specifically disclosed herein.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
22